










2.54mm DIN 41612 Connector, Flat Cable and Round Cable Application and Promotion

<p style="text-align: center;">41612-64AC-FS-IDC DIN 41612 64pin A+C Female IDC Type</p>	<p style="text-align: center;">41612-64AC-FS-IDC With Flat Cable Connector UL No. is E144392 Flat Cable 830-12-xxC UL No. is E315658, 100, 250, 500Feet/Reel</p>	<p style="text-align: center;">41612-64AC-FS-IDC Mate with 41612-64AC-MS (see below photo) 41612-64AC-FS-IDC also mate with 41612-64AC-MR R/A</p>
		
<p style="text-align: center;">41612-48ABC-MS DIN 41612 48pin ABC Male Straight</p>	<p style="text-align: center;">Female Molding Round Cable 41612-48ABC-FS DIN 41612 Three rows A+B+C Female Str.</p>	<p style="text-align: center;">41612-48ABC-MS Round Cable Mate 41612-48ABC-FS</p>
		
<p style="text-align: center;">41612-48ABC-FS DIN 41612 48pin ABC Female Straight</p>	<p style="text-align: center;">Male Molding Round Cable 41612-48ABC-MS DIN 41612 Three rows A+B+C Male Str.</p>	<p style="text-align: center;">41612-48ABC-FS Round Cable Mate 41612-48ABC-MS</p>
		

For more information, contact us to: bce@bce.it ; or browse into our website: www.bce.it

(January, 2009)