



## High Current Connectors

### WS Connectors:



### Features:

- Available Shell Size: 12mm, 20mm, 24mm, 28mm, 32mm, 40mm, 48mm, 55mm
- Metal Material
- Mated Dust Cap Available
- Available Pin Number: 2, 3, 4, 5, 7, 9, 10, 12, 13, 15, 16, 17, 19, 20, 26, 27, 31, 38, 40, 42, 53, 61
- **Rated Current/Voltage: 5A-200A**
- Operation Limit Voltage (AC.V. rms): 500V
- Withstanding Voltage (AC.V) 1 min: 1200V-1500V
- Contact Resistance (M Ohm Maximum): 0.02 - 5
- Insulation Resistance (M Ohm Minimum): 2000
- Termination: Solder or Screw Available
- Style: Socket, Plug, Straight Connector, Angled Metal, Match-able Set
- IP rating: IP55, IP65, IP67
- Atmospheric pressure: 2KPa
- Life Duration > 500 times
- **CE Approvals**



For more information, contact us to: [bce@bce.it](mailto:bce@bce.it) ; or browse into our website: [www.bce.it](http://www.bce.it)

(April, 2010)

**B.C.E. S.r.l.** - Via Regina Pacis, 54/c - I 41049 Sassuolo (MO), Italy

Tel: (+39) 0536 811616

Fax: (+39) 0536 811500

E-mail: [bce@bce.it](mailto:bce@bce.it)

Web: [www.bce.it](http://www.bce.it)