















Housing Connector Molded Cable

Figure	Drawing	Part No.	Specification
		UT-D210-3P pitch=3.96mm	
		UT-D200-4P pitch=3.96mm	<ol style="list-style-type: none"> 1.Current rating 1A- 7A 2.Voltage rating 250V AC 3.Insulation Resistance 1000M Ω Min. 4.Dielectric Strength AC 1500V 1Minute
		UT-D620-5P pitch=3.96mm	
		UT-D400-6P pitch=3.96mm	
		UT-D680-6P pitch=3.0mm	<ol style="list-style-type: none"> 1.Current rating: 1A-5A 2.Voltage rating 250V AC 3.Insulation Resistance 1000M Ω Min. 4.Dielectric Strength AC 1500V 1Minute
		UT-D440-3P pitch=4.2mm	<ol style="list-style-type: none"> 1.Current rating: 1A-9A 2.Voltage rating 250V AC 3.Insulation Resistance 1000M Ω Min. 4.Dielectric Strength AC 1500V 1Minute
		UT-D190-6P pitch=4.2mm	<ol style="list-style-type: none"> 1.Current rating: 1A-9A 2.Voltage rating 250V AC 3.Insulation Resistance 1000M Ω Min. 4.Dielectric Strength AC 1500V 1Minute