




Amphenol LTW Technology Co., Ltd.

It's Time to Offer 100% Waterproof Devices...



Specification		
A ` B type	RoHS Certified	Durability: 1500 Cycles
Un-mated (Stand-Alone) IPx7	Voltage Rating: 30V rms maximum	Connector Size:
Operating Temperature: -30°C to +85°C	Current Rating: •1A minimum for contacts 2,3 & 4	SMD Thick 6.27(L) x 10.50(W) x 5.95(H) mm SMD Thin 6.27(L) x 9.10(W) x 5.05(H) mm
(SMD) method, SMD 255°C 10 S	•1.8A for contacts 1&5 and at the same time 0.5A for contacts 2,3 &4	DIP Thick 5.77(L) x 10.50(W) x 5.95(H) mm DIP Thin 5.77(L) x 9.10(W) x 5.05(H) mm

Packaging:



Tape Reel

Application:



Digital pressure monitoring



Night Vision



Tablet PC



Digital Camera and many more...

For further information, please contact:



B.C.E. s.r.l.Via Regina Pacis, 54/c - 41049 SASSUOLO (MO) Italy
Tel. +39 0536 811.616 r.a. - Fax +39 0536 811.500
www.bce.it - E-mail: bce@bce.it





About Amphenol LTW

LTW Technology, established in 1993, is a professional designer and manufacturer of waterproof connectors. Since April of 2010, LTW Technology was acquired by Amphenol Group and officially changed its company name to "Amphenol LTW Technology Co., Ltd.". Amphenol LTW has actively devoted to various outdoor and industrial applications by successfully developing high-end waterproof connectors to meet strict requirements; also has many worldwide patents and certification such as ISO 14001. ISO 9001 and NMEA 2000...etc.. Now Amphenol LTW is not merely a supplier of waterproof connectors but also a solution provider in diversified market segments.

Innovation in Waterproof Solution