

# Circular Connector AC ⚡ DC Series

## option 1

p.1-3

		
		
panel	assembly	molded
mini size		current rating <b>5A</b>

## option 2

p.4-11

		
		
panel	assembly	molded
standard size		current rating <b>5A, 10A</b>

## option 3

p.12-23

		
		
panel	assembly	molded
middle size		current rating <b>5A, 10A, 20A</b>

## option 4

p.24-32

		
		
panel	assembly	molded
large size		current rating <b>5A, 20A</b>

## option 5

p.33


























		
panel	molded	
macro size		current rating <b>25A</b>

## option 6
























p.34

	
	
assembly	
cable joiner	current rating <b>5A, 10A, 20A</b>






































**⚠ 15A+ GOOD FOR AC USE BUT NO SAFETY AGENCY APPROVAL FOR THIS CONNECTOR. FOR FURTHER INFO PLEASE CONTACT US WITH COMPLETE ELECTRICAL SPECS.**

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES	
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N	
			MATED IP67	3.2mm PCB Contacts Circular Flange			Solder Termination Field Installable		
				9.0mm PCB Contacts Circular Flange					
	 			Solder Contacts Circular Flange					
 rear mounting	 			Solder Contacts Circular Flange Rear Mounting		 	With Strain Relief 180° Molded With Cable		
	 			Molded With Cable					 
	 								
























☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2, 3, 4 & 5			ACCESSORIES	
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N	
	LTWAD-PMMP-LS7001		MATED IP67	3.2mm PCB Contacts Square Flange		LTWAD-BFFA-LL7001	Solder Termination Field Installable		
	LTWAD-PMMP-LS7002 <i>(New)</i>			9.0mm PCB Contacts Square Flange					
	LTWAD-PMMS-LS7001 available in 2 to 3 Pins			Solder Contacts Square Flange					
	LTWASD-PMMP-LS7001				MATED IP67	PCB Contacts Square Flange			
	LTWASD-PMMS-LS7001 available in 2 to 3 Pins					Solder Contacts Square Flange			
	LTWAD-PMMP-LC7001		MATED IP67	3.2mm Contacts Circular Flange		LTWAD-AFFM-LL6AXX	With Strain Relief 180° Molded With Cable		
	LTWAD-PMMP-LC7002 <i>(New)</i>			9.0mm Contacts Circular Flange					
	LTWAD-PMMS-LC7001 available in 2 to 3 Pins			Solder Contacts Circular Flange					
 rear mounting	LTWAD-RMMS-LC7001				MATED IP67	Solder Contacts Circular Flange Rear Mounting			
	available in 2 to 3 Pins								
	LTWAD-PMMM-LL7AXX available in 2 to 3 Pins		MATED IP67	Molded With Cable					
available in 2 to 3 Pins									

☆ See Cable Index Page
















MALE CONNECTOR - NOT FOR PANEL					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
	LTWAD-  BMMA-LL7001   available in 2 to 3 Pins	Not Applicable	MATED IP67	Solder Termination Field Installable		LTWAD-  BFFA-LL7001   available in 2 to 3 Pins	Solder Contacts Field Installable	  AA-00-   -0-   -1L  available in 2 to 3 Pins  available in M or F Connector		
	LTWAD-  AMMM-LL6AXX   available in 2 to 3 Pins			Not Applicable	MATED IP67	With Strain Relief 180° Molded With Cable		LTWAD-  AFFM-LL6AXX   available in 2 to 3 Pins	With Strain Relief 180° Molded With Cable	  AA-    -   -   -TL  available in 2 to 3 Pins  available in M or F Connector
	LTWAD-  BMMM-LL7AXX   available in 2 to 3 Pins					Not Applicable	MATED IP67	Without Strain Relief 180° Molded With Cable	 	LTWAD-  BFFM-LL7AXX   available in 2 to 3 Pins  LTWAD-  BFFM-LR6AXX   available in 2 to 3 Pins

☆ : See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWBD-  -PMMR-SC7001 available in 4 to 8 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWBD-  -BFFA-SL7001 available in 2 to 8 Pins	Solder Termination Field Installable	 LTWCAP-DABPMXC1
	LTWBD-  -PMMS-SC7001 available in 2 to 8 Pins			Solder Contacts Circular Flange		LTWBD-  -AFFM-SR7AXX available in 2 to 8 Pins	With Strain Relief 90° Molded with Cable	 LTWCAP-WABPMSB1
 Rear Mounting	LTWBD-  -RMMS-SC7001 available in 2 to 8 Pins			Solder Contacts Circular Flange Rear Mounting		LTWBD-  -AFFM-SL6AXX available in 2 to 8 Pins	With Strain Relief 180° Molded with Cable	 LTWCAP-WABPMSD1
	LTWBD-  -PMMM-SL7AXX available in 2 to 8 Pins			Molded with Cable			LTWBD-  -BFFM-SR6AXX available in 2 to 8 Pins	Without Strain Relief 90° Molded with Cable
LTWBD-  -BFFM-SL7AXX available in 2 to 8 Pins	Molded with Cable			LTWBD-  -BFFM-SL7AXX available in 2 to 8 Pins	Without Strain Relief 180° Molded with Cable		 B-  -  -  -HSA01 available in 2 to 8 Pins	



























☆ : See Cable Index Page

# LTW WATERPROOF CIRCULAR CONNECTOR - STANDARD SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 2B 5










PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
	LTWBD-△PMMP-LC7001 LTWBD-△PMMP-LC7002 LTWBD-△PMMR-LC7001		MATED IP67	180° or 90° PCB Contacts Circular Flange 002 - 15mm PCB Contacts		LTWBD-△BFFA-LL7001  △available in 2 to 6 Pins	Solder Termination Field Installable	 LTWCAP-DABPMXC1		
	LTWBD-△PMMS-LC7001  △available in 2 to 6 Pins			Solder Contact Circular Flange					 LTWCAP-WABPMLA1	
 <p>Rear Mounting</p>	LTWBD-△RMMS-LC7001  △available in 2 to 6 Pins			MATED IP67	MATED IP67	Solder Contacts Circular Flange Rear Mounting	 	LTWBD-△AFFM-LR7AXX △available in 2 to 6 Pins	With Strain Relief 90° Molded with Cable	 LTWCAP-WABPMLB1
						△available in 2 to 6 Pins		Solder Contacts Circular Flange Rear Mounting	 	LTWBD-△AFFM-LL6AXX △available in 2 to 6 Pins
	LTWBD-△PMMM-LL7AXX  △available in 2 to 6 Pins					MATED IP67	MATED IP67	Molded with Cable	 	LTWBD-△BFFM-LR6AXX △available in 2 to 6 Pins
				Molded with Cable	LTWBD-△BFFM-LL7AXX △available in 2 to 6 Pins			180° Molded with Cable Without Strain Relief		 B-△△△△-HSA01 △available in 2 to 6 Pins

☆ : See Cable Index Page





















# LTW WATERPROOF CIRCULAR CONNECTOR - STANDARD SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 2C 6












PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWBD-  -PMFP-LC7001 available in 2 to 6 Pins		UNMATED IP67	PCB Contact Circular Flange		LTWBD-  -BFMA-LL7001 available in 2 to 6 Pins	Solder Termination Field Installable	 LTWCAP-DABPMXC1
	LTWBD-  -PMFS-LC7001 available in 2 to 6 Pins			Solder Contact Circular Flange				 LTWCAP-WABPMLA1
 Rear Mounting	LTWBD-  -RMFS-LC7001 available in 2 to 6 Pins			Solder Contacts Circular Flange Rear Mounting		LTWBD-  -AFMM-LR7AXX available in 2 to 6 Pins	With Strain Relief 90° Molded with Cable	 LTWCAP-WABPMLB1
				LTWBD-  -AFMM-LG6AXX available in 2 to 6 Pins		With Strain Relief 180° Molded with Cable	 LTWCAP-WABPMLD1	
	LTWBD-  -PMFM-LL7AXX available in 2 to 6 Pins			Molded with Cable		LTWBD-  -BFMM-LRG6AXX available in 2 to 6 Pins	Without Strain Relief 90° Molded with Cable	 LTWCAP-WABPMLD1
				LTWBD-  -BFMM-LL7AXX available in 2 to 6 Pins		Without Strain Relief 180° Molded with Cable	 LTWTOL-171801	
								 B-  -HSA01 available in 2 to 6 Pins

☆ : See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	ITWBSD-△PMMP-SC7001 △available in 4 to 8 Pins		UNMATED IP67	PCB Contacts Circular flange Shielded		☆ ITWBSD-△BFFM-SRGAXX	90° Molded with Cable Shielded	 ITWCAP-DABPMXA
	ITWBSD-△PMMS-SC7001 △available in 4 to 8 Pins			Solder Contacts Circular Flange Shielded		△available in 4 to 8 Pins		 ITWCAP-DABPMXA
 <p>Rear Mounting</p>	ITWBSD-△RMMS-SC7001 △available in 6 to 8 Pins			Solder Contacts Circular Flange Shielded		☆ ITWBD-△BFFM-SL7AXX	180° Molded with Cable Shielded	 ITWCAP-WABPMSB1
	ITWBSD-△PMMP-SS7001 △available in 4 to 8 Pins			PCB Contacts Square flange Shielded		△available in 4 to 8 Pins		 ITWCAP-WABPMSD1
ITWBSD-△PMMS-SS7001 △available in 4 to 8 Pins	Solder Contacts Square Flange Shielded			△available in 4 to 8 Pins		☆ △available in 4 to 8 Pins		














☆ : See Cable Index Page

PANEL (CHASSIS) MOUNT-MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWBB-  PMMP-SC7001 available in 2 to 4 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWBB-  BFFA-SL7001 available in 2 to 4 Pins	Solder Termination Field Installable	
	LTWBB-  PMMS-SC7001 available in 2 to 4 Pins			Solder Contacts Circular Flange		With Strain Relief 90° Molded with Cable		
 <p>Rear Mounting</p>	LTWBB-  RMMS-SC7001 available in 2 to 4 Pins			Solder Contacts Circular Flange Rear Mounting		LTWBB-  AFFM-SR7AXX available in 2 to 4 Pins	With Strain Relief 180° Molded with Cable	
	LTWBB-  PMMM-SL7AXX available in 2 to 4 Pins			Molded With Cable			LTWBB-  BFFM-SR6AXX available in 2 to 4 Pins	90° Molded with Cable
LTWBB-  BFFM-SL7AXX available in 2 to 4 Pins	180° Molded with Cable			B-     -MSA01 available in 2 to 4 Pins				

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	1 LTWBB-PMFP-SC7001 available in 2 to 3 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWBB-BFMA-SL7001 available in 2 to 3 Pins	Solder termination Field Installable	 LTWCAP-DABPMXC1  LTWCAP-WABPMLB1  LTWCAP-WABPMLD1  LTWTUL-171801  B-MSA01 available in 2 to 3 Pins
	LTWBB-PMFS-SC7001 available in 2 to 3 Pins			Solder Contacts Circular Flange				
 Rear Mounting	2 LTWBB-RMFS-SC7001 available in 2 to 3 Pins			Solder Contacts Circular Flange Rear Mounting		LTWBB-AFMM-SL6AXX available in 2 to 3 Pins	☆ With Strain Relief 180° Molded with Cable	
	3 LTWBB-PMFM-SL7AXX available in 2 to 3 Pins			Molded With Cable				















☆ See Cable Index Page

# LTW WATERPROOF CIRCULAR CONNECTOR - STANDARD SIZE 1/4 TURN LOCK BAYONET TYPE (10A) - OPTION 2G 10

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES			
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N			
	LTWBB-△PMMP-LC7001 LTWBB-△PMMP-LC7002 △available in 2 to 4 Pins		MATED IP67	PCB Contacts Circular Flange  002 - 15mm PCB Contacts		LTWBB-△BFFA-LL7001  △available in 2 to 4 Pins	Solder Termination Field Installable	 LTWCAP-DABPMXC1  LTWCAP-WABPMLA1			
	LTWBB-△PMMS-LC7001  △available in 2 to 4 Pins			Solder Contacts Circular Flange		△available in 2 to 4 Pins					
 Rear Mounting	LTWBB-△RMMS-LC7001  △available in 2 to 4 Pins			Solder Contacts Circular Flange Rear Mounting		LTWBB-△AFFM-LR7AAX ☆ △available in 2 to 4 Pins	With Strain Relief 90° Molded with Cable		 LTWCAP-WABPMLB1		
	△available in 2 to 4 Pins			Solder Contacts Circular Flange Rear Mounting			LTWBB-△AFFM-LL6AAX ☆ △available in 2 to 4 Pins		With Strain Relief 180° Molded with Cable	 LTWCAP-WABPMLD1	
	LTWBB-△PMMM-LL7AAX ☆  △available in 2 to 4 Pins					Molded With Cable			LTWBB-△BFFM-LR6AAX ☆ △available in 2 to 4 Pins	90° Molded with Cable Without Strain Relief	 LTWTOL-171801
	△available in 2 to 4 Pins					Molded With Cable			LTWBB-△BFFM-LL7AAX ☆ △available in 2 to 4 Pins	180° Molded with Cable Without Strain Relief	 B-△△△△-HSA01 △available in 2 to 6 Pins















☆ : See Cable Index Page

LTW WATERPROOF CIRCULAR CONNECTOR - STANDARD SIZE 1/4 TURN LOCK BAYONET TYPE (10A) - OPTION 2H 11

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWBB-△PMFP-LC7001 LTWBB-△PMFP-LC7002 △available in 2 to 3 Pins		UNMATED IP67	PCB Contacts Circular Flange 002 - 15mm PCB Contacts		LTWBB-△BFMA-LL7001 △available in 2 to 3 Pins	Solder Termination Field Installable	 LTWCAP-DABPMXC1  LTWCAP-WABPMLA1
	LTWBB-△PMFS-LC7001 △available in 2 to 3 Pins			Solder Contacts Circular Flange			LTWBB-△AFMM-LR7AXX ☆ With Strain Relief 90° Molded with Cable	 LTWCAP-WABPMLB1
 <p>Rear Mounting</p>	LTWBB-△RMFS-LC7001 △available in 2 to 3 Pins			Solder Contacts Circular Flange Rear Mounting	Molded With Cable		LTWBB-△AFMM-LL6AXX ☆ With Strain Relief 180° Molded with Cable △available in 2 to 3 Pins	 LTWCAP-WABPMLD1
	☆ LTWBB-△PMFM-LL7AXX △available in 2 to 3 Pins			Molded With Cable				LTWBB-△BFMM-LR6AXX ☆ 90° Molded with Cable
☆ LTWBB-△PMFM-LL7AXX △available in 2 to 3 Pins : See Cable Index Page	Molded With Cable					LTWBB-△BFMM-LL7AXX ☆ 180° Molded with Cable △available in 2 to 3 Pins	 LTWTOL-171801  B-△△△△-HSA01 △available in 2 to 6 Pins	












PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWCD-PMMP-SC7001 available in 7 to 10,12,14 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWCD-AFFM-SL7AXX available in 7 to 10,12,14 Pins	With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMSA1  LTWCAP-WCCPMSB1
	LTWCD-PMMS-SC7001 available in 7 to 10,12,14 Pins			Solder Contacts Circular Flange		LTWCD-BFFM-SL6AXX available in 7 to 10,12,14 Pins	180° Molded with Cable	 LTWCAP-WCCPMSB1  LTWCAP-WCCPMSB1
 <p>Rear Mounting</p>	LTWCD-RMMS-SC7001 available in 7 to 10,12,14 Pins			Solder Contacts Circular Flange Rear Mounting		LTWCD-BFFM-SL6AXX available in 7 to 10,12,14 Pins	180° Molded with Cable	 LTWCAP-WCCPMSB1  LTWTOL-171801
	LTWCD-PMMM-SL7AXX available in 7 to 10,12,14 Pins			180° Molded with Cable		LTWCD-BFFA-SL7001 available in 7 to 10,12,14 Pins	Field Installable Solder Termination	 LTWCAP-DACCKC  LTWCAP-DACPMXC

☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
 <p>1</p>	LTWCD-△PMFP-SC7001 △available in 7 to 9 Pins	 <p>19.4±0.1</p> <p>ø20.8±0.1</p>	UNMATED IP67	PCB Contacts Circular Flange		LTWCD-△PMFP-SC7001 △available in 7 to 9 Pins	☆  With Strain Relief 180° Molded with Cable	 ITWCAP-WCCPMSA1		
	LTWCD-△PMFS-SC7001 △available in 7 to 9 Pins			Solder Contacts Circular Flange		LTWCD-△AFMM-SL7AXX △available in 7 to 9 Pins		 ITWCAP-WCCPMSB1		
 <p>2</p> <p>Rear Mounting</p>	LTWCD-△RMFS-SC7001 △available in 7 to 9 Pins			Solder Type 5A Current Rating Rear Mounting		LTWCD-△BFMM-SL6AXX △available in 7 to 9 Pins	☆  180° Molded with Cable	 ITWCAP-WCCPMSB1		
	LTWCD-△BFMM-SL6AXX △available in 7 to 9 Pins			180° Molded with Cable		LTWCD-△BFMM-SL6AXX △available in 7 to 9 Pins	☆  180° Molded with Cable	 ITWCAP-WCCPMSC1		
 <p>3</p>	LTWCD-△PMFM-SL7AXX △available in 7 to 9 Pins					180° Molded with Cable		LTWCD-△BFMA-SL7001 △available in 7 to 9 Pins	Field Installable Solder Termination	 ITWTOL-171801
								LTWCD-△BFMA-SL7001 △available in 7 to 9 Pins	Field Installable Solder Termination	 ITWCAP-DACCCX
								 ITWCAP-DACPMXC		














☆ See Cable Index Page

# LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 3C 14

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
 <p>1</p>	LTWCD-PMMP-LC7001 available in 7 to 10,12,14 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWCD-AFFM-LL7AXX available in 7 to 10,12,14 Pins	With Strain Relief 180° Molded with Cable	 <p>ITWCAP-WCCPMLA1</p>		
	LTWCD-PMMS-LC7001 available in 7 to 10,12,14 Pins			Solder Contacts Circular Flange				 <p>ITWCAP-WCCPMLB1</p>		
 <p>2</p> <p>Rear Mounting</p>	LTWCD-RMMS-LC7001 available in 7 to 10,12,14 Pins			Solder Contacts Circular Flange Rear Mounting		LTWCD-BFFM-LL6AXX available in 7 to 10,12,14 Pins	180° Molded with Cable	 <p>ITWCAP-WCCPMLC1</p>		
	available in 7 to 10,12,14 Pins			 <p>ITWCAP-WCCPMLD1</p>						
 <p>3</p>	LTWCD-PMMM-LL7AXX available in 7 to 10,12,14 Pins					180° Molded with Cable		LTWCD-BFFA-LL7001 available in 7 to 10,12,14 Pins	Field Installable Solder Termination	 <p>ITWTOL-171801</p>
available in 7 to 10,12,14 Pins	 <p>ITWCAP-DACCXC</p>									
								 <p>ITWCAP-DACPMXC</p>		

☆ : See Cable Index Page

LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 3D 15

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWCD-△PMFP-LC7001 △ available in 7 to 9 Pins		UNMATED IP67	PCB Contacts Circular Flange		☆ LTWCD-△AFMM-LL7AXX △ available in 7 to 9 Pins	☆ With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMLA1  LTWCAP-WCCPMLB1 
	LTWCD-△PMFS-LC7001 △ available in 7 to 9 Pins			Solder Contacts Circular Flange		△ available in 7 to 9 Pins	 LTWCAP-WCCPMLC1  LTWCAP-WCCPMLD1	
 <p>Rear Mounting</p>	LTWCD-△RMFS-LC7001 △ available in 7 to 9 Pins			Solder Contacts Circular Flange Rear Mounting		☆ LTWCD-△BFMM-LL6AXX △ available in 7 to 9 Pins	☆ 180° Molded with Cable	 LTWTOL-171801  LTWCAP-DACCXC  LTWCAP-DACPMXC
	☆ LTWCD-△PMFM-LL7AXX △ available in 7 to 9 Pins			180° Molded with Cable		☆ LTWCD-△BFMA-LL7001 △ available in 7 to 9 Pins	Field Installable Solder Contacts	

☆ See Cable Index Page

LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 3E 16






















MALE CONNECTOR - NOT FOR PANEL					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	1 LTWCD-  AMMM-LL7AXX <small>available in 7 to 10,12,14 Pins</small>	Not Applicable	UNMATED IP67	With Strain relief 180° Molded with Cable		☆ LTWCD-  AFMM-LL7AXX <small>available in 7 to 10,12,14 Pins</small>	With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMLA1  LTWCAP-WCCPMLB1 
	2 LTWCD-  BMMM-LL6AXX <small>available in 7 to 10,12,14 Pins</small>		UNMATED IP66	180° Molded with Cable		☆ LTWCD-  BFMM-LL6AXX <small>available in 7 to 10,12,14 Pins</small>	180° Molded with Cable	 LTWCAP-WCCPMLC1  LTWCAP-WCCPMLD1 
	3 LTWCD-  BMMA-LL7001 <small>available in 7 to 10,12,14 Pins</small>		MATED IP67	Solder Termination Field Installable		LTWCD-  BFMA-LL7001 <small>available in 7 to 10,12,14 Pins</small>	Field Installable Solder Termination	 LTWTOL-171801  LTWCAP-DACCXC  LTWCAP-DACPMXC

☆ See Cable Index Page
























LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (5A) - OPTION 3F 17

MALE CONNECTOR - NOT FOR PANEL					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
	LTWCD-  AMFM-LL7AXX   available in 7 to 9 Pins	☆  Not Applicable	UNMATED IP67	With Strain relief 180° Molded with Cable		LTWCD-  AFMM-LL7AXX   available in 7 to 9 Pins	With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMLA1  LTWCAP-WCCPMLB1  LTWCAP-WCCPMLC1  LTWCAP-WCCPMLD1		
	LTWCD-  BMFM-LL6AXX   available in 7 to 9 Pins			☆  Not Applicable	UNMATED IP66	Without Strain relief 180° Molded with Cable		LTWCD-  BFMM-LL6AXX   available in 7 to 9 Pins	Without Strain Relief 180° Molded with Cable	 LTWTOL-171801  LTWCAP-DACCKC  LTWCAP-DACPMXC
	LTWCD-  BMFA-LL7001   available in 7 to 9 Pins					☆  Not Applicable	MATED IP67	Solder Termination Field Installable		LTWCD-  BFMA-LL7001   available in 7 to 9 Pins







☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES	
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N	
 <p><b>1</b></p>	LTWCB-  -PMMP-SC7001 available in 4 to 6 Pins		UNMATED IP67	PCB Contacts Circular Flange	 <p>LTWCB--AFFM-SL7AXX</p> available in 4 to 6 Pins	☆ With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMSA1  LTWCAP-WCCPMSB1  LTWCAP-WCCPMS1  LTWCAP-WCCPMSD1  ITWTOL-171801  LTWCAP-DACCXC  LTWCAP-DACPMXC		
	LTWCB-  -PMMS-SC7001 available in 4 to 6 Pins			Solder Contacts Circular Flange					
 <p><b>2</b></p>	LTWCB-  -RMMS-SC7001 available in 4 to 6 Pins			Solder Contacts Circular Flange Rear Mounting	 <p>LTWCB--BFFM-SL6AXX</p> available in 4 to 6 Pins	☆ 180° Molded with Cable			
	☆ available in 4 to 6 Pins			180° Molded with Cable					
 <p><b>3</b></p>	LTWCB-  -PMMM-SL7AXX available in 4 to 6 Pins			☆ available in 4 to 6 Pins	☆ available in 4 to 6 Pins	180° Molded with Cable		 <p>LTWCB--BFFA-SL7001</p> available in 4 to 6 Pins	Field Installable Solder Termination





















☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWCB-  PMFP-SC7001		UNMATED IP67	PCB Contacts Circular Flange		 LTWCB-  AFMM-SL7AXX available in 4 to 5 Pins	With Strain Relief 180° Molded with Cable	 LTWCAP-WCCPMSA1
	LTWCB-  PMFS-SC7001 available in 4 to 5 Pins			Solder Contacts Circular Flange				 LTWCAP-WCCPMSB1
	LTWCB-  RMFS-SC7001			available in 4 to 5 Pins Rear Mounting	Solder Contacts Circular Flange Rear Mounting		 LTWCB-  BFMM-SLGAXX available in 4 to 5 Pins	180° Molded with Cable
	LTWCB-  PMFM-SL7AXX			180° Molded with Cable		 LTWCB-  BFMA-SL7001 available in 4 to 5 Pins	Field Installable Solder Termination	 LTWTOL-171801   LTWCAP-DACCKC   LTWCAP-DACPMAC






 See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	<b>1</b> LTWCB-PMMP-LC7001 available in 4 to 6 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWCB-AFFM-LL7AXX available in 4 to 6 Pins	With Strain Relief 180° Molded with Cable	 ITWCAP-WCCPMLA1
	LTWCB-PMMS-LC7001 available in 4 to 6 Pins			Solder Contacts Circular Flange		LTWCB-BFFM-LL6AXX available in 4 to 6 Pins	 ITWCAP-WCCPMLB1	
<b>2</b> LTWCB-RMMS-LC7001 Rear Mounting available in 4 to 6 Pins	Solder Contacts Circular Flange Rear Mounting				LTWCB-BFFM-LL6AXX available in 4 to 6 Pins	180° Molded with Cable  ITWCAP-WCCPMLC1		
<b>3</b> 	LTWCB-PMMM-LL7AXX available in 4 to 6 Pins			180° Molded with Cable		LTWCB-BFFA-LL7001 available in 4 to 6 Pins	Field Installable Solder Termination  ITWCAP-WCCPMLD1  ITWTOL-171801  ITWCAP-DACCXC  ITWCAP-DACPMXC	

# LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (10A) - OPTION 3J 21
















PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES		
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N		
 <p>1</p>	LTWCB-△PMFP-LC7001 △available in 4 to 5 Pins	 <p>19.4±0.1</p> <p>ø20.8±0.1</p>	UNMATED IP67	PCB Contacts Circular Flange		LTWCB-△AFMM-LL7AXX ☆ △available in 4 to 5 Pins	With Strain Relief 180° Molded with Cable	 ITWCAP-WCCPMLA1  ITWCAP-WCCPMLB1  ITWCAP-WCCPMLC1  ITWCAP-WCCPMLD1		
	LTWCB-△PMFS-LC7001 △available in 4 to 5 Pins			Solder Contacts Circular Flange		LTWCB-△BFMM-LL6AXX ☆ △available in 4 to 5 Pins	180° Molded with Cable	 ITWTOL-171801  ITWCAP-DAGCXC  ITWCAP-DACPMXC		
 <p>2</p> <p>Rear Mounting</p>	LTWCB-△RMFS-LC7001 △available in 4 to 5 Pins			Solder Contacts Circular Flange Rear Mounting		LTWCB-△BFMM-LL6AXX ☆ △available in 4 to 5 Pins	180° Molded with Cable	 ITWTOL-171801  ITWCAP-DAGCXC  ITWCAP-DACPMXC		
 <p>3</p>	LTWCB-△PMFM-LL7AXX ☆ △available in 4 to 5 Pins					180° Molded with Cable		LTWCB-△BFMA-LL7001 ☆ △available in 4 to 5 Pins	Solder Contacts Field Installable	 ITWTOL-171801  ITWCAP-DAGCXC  ITWCAP-DACPMXC

☆ : See Cable Index Page
















PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
 <p>1</p>	LTWCC-03PMP-SC7001			PCB Contacts Circular Flange	 <p>☆</p>	LTWCC-03AFFM-SL7AXX	with Strain Relief 180° Molded with Cable	 <p>ITWCAP-WCCPMSA1</p>  <p>ITWCAP-WCCPMSB1</p>
 <p>2</p>	LTWCC-03PMMS-SC7001	 <p>19.4 ± 0.1 ø20.8 ± 0.1</p>	UNMATED IP67	Solder Contacts Circular Flange	 <p>☆</p>	LTWCC-03BFFM-SL6AXX	180° Molded with Cable	 <p>ITWCAP-WCCPMSB1</p>  <p>ITWCAP-WCCPMSC1</p>  <p>ITWCAP-WCCPMSD1</p>
 <p>3</p> <p>Rear Mounting</p>	LTWCC-03RMMS-SC7001			Solder Contacts Circular Flange Rear Mounting	 <p>☆</p>	LTWCC-03BFFA-SL7001	Field Installable Solder Termination	 <p>ITWTOL-171801</p>  <p>ITWCAP-DACCXC</p>  <p>ITWCAP-DACPMXC</p>
















LTW WATERPROOF CIRCULAR CONNECTOR - MIDDLE SIZE 1/4 TURN LOCK BAYONET TYPE (20A) - OPTION 3L 23

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
 <p>1</p>	ITWCC-03PMP-IC7001			PCB Contacts Circular Flange		ITWCC-03AFFM-LL7AXX	with Strain Relief 180° Molded with Cable	 <p>ITWCAP-WCCPMLA1</p>  <p>ITWCAP-WCCPMLB1</p>
 <p>2</p>	ITWCC-03PMMS-IC7001	 <p>19.4±0.1 ø20.8±0.1</p>	UNMATED IP67	Solder Contacts Circular Flange		ITWCC-03BFFM-LL6AXX	180° Molded with Cable	 <p>ITWCAP-WCCPMLC1</p>  <p>ITWCAP-WCCPMLD1</p>
 <p>3</p> <p>Rear Mounting</p>	ITWCC-03RMMS-IC7001			SOLDER CONTACTS CIRCULAR FLANGE REAR MOUNTING		ITWCC-03BFFA-LL7001	Field Installable Solder Termination	 <p>ITWTOL-171801</p>  <p>ITWCAP-DACCXC</p>  <p>ITWCAP-DACPMXC</p>
















PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWDD-18PMMP-SC7001		UNMATED IP67	PCB Contacts Circular Flange		LTWDD-18AFFM-SL7AXX <span style="color:red">☆</span>	With Strain Relief 180° Molded with Cable	 LTWCAP-WADPMSA1
	LTWDD-18PMMS-SC7001			Solder Contacts Circular Flange		LTWDD-18AFFM-SR7AXX <span style="color:red">☆</span>	With Strain Relief 90° Molded with Cable	 LTWCAP-WADPMSB1
	LTWDD-18PMMP-SS7001			PCB Contacts Square Flange		LTWDD-18BFFM-SL6AXX <span style="color:red">☆</span>	180° Molded with Cable	 LTWCAP-WADPMSC1
	LTWDD-18PMMS-SS7001			Solder Contacts Square Flange				 LTWCAP-WADPMSD1
 <p>Rear Mounting</p>	LTWDD-18RMMS-SC7001			Solder Contacts Rear Mounting Circular Flange		LTWDD-18BFFA-SL7001	Field Installable Solder Termination	 LTWTOL-222901   LTWCAP-DADPMKC

☆ See Cable Index Page













PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWDD-18PMFP-SC7001		UNMATED IP67	PCB Contacts Circular Flange		☆ LTWDD-18AFMM-SL7AXX	With Strain Relief 180° Molded with Cable	 ITWCAP-WADPMSA1
	LTWDD-18PMFS-SC7001			Solder Contacts Circular Flange				 ITWCAP-WADPMSB1
	LTWDD-18PMFP-SS7001			PCB Contacts Square Flange		☆ LTWDD-18BFMM-SL6AXX	Without Strain Relief 180° Molded with Cable	 ITWCAP-WADPMSC1
	LTWDD-18PMFS-SS7001			Solder Contacts Square Flange				 ITWCAP-WADPMSD1
 <p>Rear Mounting</p>	LTWDD-18RMFS-SC7001			Solder Contacts Rear Mounting Circular Flange		LTWDD-18BFMA-SL7001	Field Installable Solder Termination	 ITWTOL-222901   ITWCAP-DADPMXC

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWDD-18PMMP-LC7001		UNMATED IP67	PCB Contacts Circular Flange		LTWDD-18AFFM-LL7AXX <span style="color:red">☆</span>	With Strain Relief 180° Molded with Cable	 <b>ITWCAP-WADPMLA1</b>
	LTWDD-18PMMS-LC7001			Solder Contacts Circular Flange		LTWDD-18AFFM-LR7AXX <span style="color:red">☆</span>	With Strain Relief 90° Molded with Cable	 <b>ITWCAP-WADPMLB1</b>
	LTWDD-18PMMP-LS7001			PCB Contacts Square Flange		LTWDD-18BFFM-LL6AXX <span style="color:red">☆</span>	180° Molded with Cable	 <b>ITWCAP-WADPMLC1</b>
	LTWDD-18PMMS-LS7001			Solder Contacts Square Flange		 <b>ITWCAP-WADPMLD1</b>		
 <p>Rear Mounting</p>	LTWDD-18RMMS-LC7001			Solder Contacts Rear Mounting Circular Flange		LTWDD-18BFFA-LL7001	Field Installable Solder Termination	 <b>LTWTOL-222901</b>  <b>ITWCAP-DADPMXC</b>



☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2, 3 & 4			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWDD-18PMFP-LC7001		UNMATED IP67	PCB Contacts Circular Flange		LTWDD-18AFMM-LL7AXX	With Strain Relief 180° Molded with Cable	 <b>LTWCAP-WADPMLA1</b>
	LTWDD-18PMFS-LC7001			Solder Contacts Circular Flange		LTWDD-18BFMM-LL6AXX	180° Molded with Cable	 <b>LTWCAP-WADPMLB1</b>
	LTWDD-18PMFP-LS7001			PCB Contacts Square Flange		LTWDD-18BFMA-LL7001	Field Installable Solder Termination	 <b>LTWTOL-222901</b>
	LTWDD-18PMFS-LS7001			Solder Contacts Square Flange				 <b>LTWCAP-DADPMXC</b>





☆ See Cable Index Page

MALE CONNECTOR - NOT FOR PANEL					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	ITWDD-18PMMM-LL7AXX	Not Applicable	MATED IP67	with Strain Relief 180° Molded with Cable		ITWDD-18AFFM-LL7AXX	with Strain Relief 180° Molded with Cable	 ITWCAP-WADPMLA1
						ITWDD-18AFFM-LR7AXX	with Strain Relief 90° Molded with Cable	 ITWCAP-WADPMLB1
	ITWDD-18BMMM-LL6AXX	Not Applicable	MATED IP66	without Strain Relief 180° Molded with Cable		ITWDD-18BFFM-LL6AXX	180° Molded with Cable	 ITWCAP-WADPMLC1
	ITWDD-18BMMMA-LL7001	Not Applicable	MATED IP67	Solder Termination Field Installable		ITWDD-18BFFA-LL7001	Field Installable Solder Termination	 ITWTOL-222901   ITWCAP-DADPMXC

























☆ See Cable Index Page

MALE CONNECTOR - NOT FOR PANEL					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	ITWDD-18AMFM-LL7AXX		UNMATED IP67	with Strain Relief 180° Molded with Cable		ITWDD-18AFMM-LL7AXX	with Strain Relief 180° Molded with Cable	 <b>ITWCAP-WADPMLA1</b>  <b>ITWCAP-WADPMLB1</b>
	ITWDD-18BMFM-LL6AXX	Not Applicable	UNMATED IP66	180° Molded with Cable		ITWDD-18BFMM-LL6AXX	180° Molded with Cable	 <b>ITWCAP-WADPMLC1</b>  <b>ITWCAP-WADPMLD1</b>
	ITWDD-18BMFA-LL7001		UNMATED IP67	Solder Termination Field Installable		ITWDD-18BFMA-LL7001	Field Installable Solder Termination	 <b>ITWTOL-222901</b>  <b>ITWCAP-DADPMXC</b>























☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWDS0-18PMFP-SS7001		UNMATED IP67	PCB Contacts Square Flange Shielded		LTWDS0-18BFMM-SL7AXX	180° Molded with Cable Shielded	
	LTWDS0-18PMFS-SS7001			Solder Contacts Square Flange Shielded		LTWDS0-18BFMM-SRGAXX	90° Molded with Cable Shielded	



☆ See Cable Index Page

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
 <p>1</p>	LTWDC-  PMMP-SC7001 available in 2 to 7 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWDC-  AFFM-SL7AXX available in 2 to 7 Pins	with Strain Relief 180° Molded with Cable	 <p>LTWCAP-WADPMSA1</p>
	LTWDC-  PMMS-SC7001 available in 2 to 7 Pins			Solder Contacts Circular Flange				 <p>LTWCAP-WADPMSB1</p>
 <p>2</p>	LTWDC-  PMMP-SS7001 available in 2 to 7 Pins			PCB Contacts Square Flange		LTWDC-  BFFM-SL6AXX available in 2 to 7 Pins	180° Molded with Cable	 <p>LTWCAP-WADPMSC1</p>
	LTWDC-  PMMS-SS7001 available in 2 to 7 Pins			Solder Contacts Square Flange				 <p>LTWCAP-WADPMSD1</p>
 <p>3</p>	LTWDC-  RMMS-SC7001 available in 2 to 7 Pins Rear Mounting			Solder Contacts Circular Flange Rear Mounting		LTWDC-  BFFA-SL7001 LTWDC-  BFFB-SL7001 available in 2 to 7 Pins	Field Installable Solder Termination Field Installable Screw-in Termination	 <p>LTWTOL-222901</p>  <p>LTWCAP-DADPMXC</p>

See Cable Index Page  GOOD FOR AC USE BUT NO SAFETY AGENCY APPROVAL FOR THIS CONNECTOR. FOR FURTHER INFO PLEASE CONTACT US WITH COMPLETE ELECTRICAL SPECS. © 2006 LTW Subic Bay Own Brand Team

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS OF 1, 2 & 3			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
 <p><b>1</b></p>	LTWDC-  PMMP-LC7001 available in 2 to 7 Pins		UNMATED IP67	PCB Contacts Circular Flange		LTWDC-  AFFM-LL7AXX available in 2 to 7 Pins	with Strain Relief 180° Molded with Cable	 LTWCAP-WADPMLA1
	LTWDC-  PMMS-LC7001 available in 2 to 7 Pins			Solder Contacts Circular Flange				available in 2 to 7 Pins
 <p><b>2</b></p>	LTWDC-  PMMP-LS7001 available in 2 to 7 Pins			PCB Contacts Square Flange		LTWDC-  BFFM-LL6AXX available in 2 to 7 Pins	180° Molded with Cable	 LTWCAP-WADPMLC1
	LTWDC-  PMMS-LS7001 available in 2 to 7 Pins			Solder Contacts Square Flange				available in 2 to 7 Pins
 <p><b>3</b></p>	LTWDC-  RMMS-LC7001 available in 2 to 7 Pins			Solder Contacts Circular Flange Rear Mounting		LTWDC-  BFFA-LL7001 LTWDC-  BFFB-LL7001 available in 2 to 7 Pins	Field Installable Solder Termination  Field Installable Screw-in Termination	 LTWTOL-222901   LTWCAP-DADPMXC

 GOOD FOR AC USE BUT NO SAFETY AGENCY APPROVAL FOR THIS CONNECTOR. FOR FURTHER INFO PLEASE CONTACT US WITH COMPLETE ELECTRICAL SPECS. © 2006 LTW Subic Bay Own Brand Team

PANEL (CHASSIS) MOUNT - MALE CONNECTOR					MATING PAIRS			ACCESSORIES
CONNECTOR	P/N	PANEL CUT-OUT	IP RATING	FEATURES	CONNECTOR	P/N	FEATURES	P/N
	LTWPWH-03PMMS-SC7001		MATED IP67	Screw-in Contacts Circular Flange		LTWPWH-03AFFM-SL7AKX	180° Molded with Cable With Strain Relief	



## LTWCX-04BAM20-7001

10.0  
3.0

Recommended Cable Gauge:  
18AWG to 24AWG

**1 Strip Cable sheath and insulation.**

**2 Insert Cable strip ends into Cable Joiner parts as shown.**

press down

**3 Insert the Conductors of Cable 1 into Butt Connector and press down to clip the wire.**

**Name of Parts**

Sealing Nut  
Cable 2  
Seal  
Housing  
Clamp Ring  
Seal  
Butt Connector  
Conductor  
Cable 1  
Sealing Nut

Recommended Hand Tool:  
LTWTOL-222901

**Features:** Mating Style: Screw Type  
IP Rating: 67  
No. of Cable conductors it can connect: 2 to 4

press down

**4 Insert the Conductors of Cable 2 into the other end of Butt Connector and press down to clip.**

⚠️ for Safety, it is advisable that conductor colors should match!

**7 Connect Sealing Nuts to the opposite ends of Clamp Ring. Tighten using Hand Tool (optional) or hand while holding assy.**

**6 Move the Housing and Seals into the Clamping as shown.**

insert

**5 Mount the Butt Connectors with the clipped Conductors to Housing.**

Questions?



Valued Quality. Delivered.



Tack                      Vielen Dank  
Obrigado  
Merci                      ありがとうございます  
Bedankt                      感謝您  
Takk                      谢谢  
Grazie                      谢谢  
Спасибо                      谢谢  
Kiitos                      Thank You  
Tak                      谢谢  
Gracias                      감사합니다  
Dziękujemy                      Σας ευχαριστούμε

**Email:** [bce@bce.it](mailto:bce@bce.it)

**Website:** [www.bce.it](http://www.bce.it)