

Snap-In VENT

Fast, Secure Installation & Reliable Protection




Amphenol LTW (ALTW) introduces the Snap-In Vent providing fast, secure installation and IP68/IP69K waterproof rated for your outdoor enclosure in harsh environments.

With hydrophobic and oleophobic membrane, ALTW Snap-In Vent keeps liquids, oils, and moisture out, and effectively equalizes pressure and reduces condensation in sealed enclosure, for the purpose of protecting outdoor electronic devices and extending their service life.

VENT | Applications



Industrial Automation



Renewable Energy



Outdoor Broadband Wireless Access




LED Lighting



IP Closed-circuit Television (IP CCTV) & Security

Specification

Part Number		VENT-PQ1NBK-O8001 VENT-PQ1NBK-N8001 VENT-PQ1NBK-O8002 VENT-PQ1NBK-N8002	VENT-PQ1NGY-O8001 VENT-PQ1NGY-N8001 VENT-PQ1NGY-O8002 VENT-PQ1NGY-N8002
Dimension 			
Assembly Type		Snap-in	Snap-in
Specification	Environment Temperature	-40°C~+125°C	-40°C~+125°C
	Waterproof Rating	IP68 (2M · 60mins), IP69K	IP68 (2M · 60mins), IP69K
	Air Permeability	> 550 - 3000ml/min @70mbar	> 550 - 3000ml/min @70mbar
	Water Entry Pressure	> 60kPa	> 60kPa
Material	Housing	Nylon, 94V-0, UV Resistance, UL	Nylon, 94V-0, UV Resistance, UL
	Membrane	ePTFE	ePTFE
	Sealing	O-ring: Silicone	O-ring: Silicone
	Housing Color	Black	Gray

B.C.E. s.r.l.

For more information, please contact: Via Regina Pacis, 54/c - 41049 SASSUOLO (MO) Italy
Tel. +39 0536 811.616 r.a. - Fax +39 0536 811.500
www.bce.it - E-mail: bce@bce.it

Copyright © 2018 [Amphenol LTW Technology Co. Ltd](http://www.amphenol-ltw.com)

5F-3, No. 51, Section 4, Zhongyang Road, Tucheng District, New Taipei City 236 Taiwan