

48U THRU-HOLE CRYSTAL

FEATURES

- High Precision availability
- Wide Frequency Range
- Applications: Telecommunication equipment,...

19.4 x 8.95 x 19.8 mm



Item	Symbol	Specification
Frequency Range	Fo	0.8 MHz ~ 200 MHz
Operation Mode		0.8 MHz + Fundamental (see options) 15.0 MHz ~ 100.0 MHz 3rd-overtone (see options) 50.0 MHz ~ 160.0 MHz 5th-overtone (see options) 80.0 MHz ~ 200.0 MHz 7th-overtone (see options)
Operating temperature Range	To	0° to +70 °C (see options)
Frequency Tolerance at 25 °C	$\Delta f/F$	± 10 ppm max. (see options)
Temperature Stability	$\Delta f/F$	± 10 ppm max. (see options)
Load Capacitance (CL)	CL	series or 10 pF to 60 pF (see options)
Equivalent Series Resistance	ESR	Frequency dependent, please consult factory
Shunt Capacitance (Co)	Co	7pF Max
Insulation Resistance	Ri	500 M Ω min. (at 100Vdc)
Drive Level	DL	5mW max.
Aging	$\Delta f/F$	± 5 ppm max (at 25 °C, first year)
Packing Unit		Bulk in bag
		Customer specifications on request

OPTIONS & ORDERING INFORMATION

48U- MHz	-
	Freq. Tolerance	Freq. Stability*	Operating Temp.*	Load Capacitance	Mode	Frequency in MHz	ESR if other than STD
	05 = ± 05 ppm	05 = ± 05 ppm	D = -10° / +60 °C	Please specify CL in pF or S for Series	F = Fundamental	Please specify the frequency in MHz	Specify a value in Ω
	10 = ± 10 ppm	10 = ± 10 ppm	E = 0° / +70 °C		D = 3rd overtone		
	15 = ± 15 ppm	15 = ± 15 ppm	F = -20° / +70 °C		V = 5th overtone		
	20 = ± 20 ppm	20 = ± 20 ppm	G = -30° / +75 °C		Z = 7th overtone		
	25 = ± 25 ppm	25 = ± 25 ppm	H = -30° / +85 °C				
	30 = ± 30 ppm	30 = ± 30 ppm	K = -40° / +85 °C				
	50 = ± 50 ppm	50 = ± 50 ppm					

* Note: Not all combinations are possible, please consult us.



B.C.E. s.r.l.
Via Regina Pacis, 54/c - 41049 SASSUOLO (MO) Italy
Tel. +39 0536 811.616 r.a. - Fax +39 0536 811.500
www.bce.it - E-mail: bce@bce.it



OUTLINE DIMENSIONS

