

M8 8 ports Junction box

- Housing material: Nylon/Black
- Coupling nut: Brass/Nickel
- Contact carrier: TPU/Black
- Pin: Brass/Gold
- O-ring: FPM/FKM, IP degree: IP67
- Load: 10~30VDC, 2 A/port, 6 A total, LED 10mA
- Temperature range: -30...+80°C
- Mechanical operation: ≥100



Dimensions/Circuit diagram	Specifications	Type NO./ID NO.
<p style="text-align: center;">MOUNTING HOLE M3 SOCKET HEAD 12mm MINIMUM LENGTH 2° PLS</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>M16</p> </div> <div style="text-align: center;"> <p>M8</p> </div> </div> <div style="margin-top: 10px;"> <p style="text-align: center;">NO LED</p> <p style="text-align: center;">JB8M8-3-M16</p> </div> <div style="margin-top: 10px;"> <p style="text-align: center;">PNP LED</p> <p style="text-align: center;">JB8M8-3P-M16</p> </div>	<p>1 signal per port NO LED M16 vertical connector</p>	<p style="text-align: center;">JB8M8-3-M16 10073150</p>
<p>1 signal per port PNP LED M16 vertical connector</p>	<p style="text-align: center;">JB8M8-3P-M16 10073151</p>	

* Standard cable lengths are 2/5/10M, Consult factory for other lengths

** Standard coupling nut material is nickel plated brass