

- Housing material:Nylon/Black
- Coupling nut:Brass/Nickel
- Contact carrier:TPU/Black
- Pin:Brass/Gold
- O-ring:FPM/FKM, IP degree:IP67
- Load:10~30VDC,2 A/port, 6 A total,LED 10mA
- Temperature range:-30...+80°C
- Mechanical operation:≥100



Dimensions/Circuit diagram	Specifications	Type NO./ID NO.
<p><b>M23 19-Pin</b></p>	<p>2 signals per port NO LED M23 vertical connector</p>	<p>JB4M12-4-T-R 10071080</p>
<p><b>Terminal connection 21-Pin</b></p>	<p>2 signals per port PNP LED M23 vertical connector</p>	<p>JB4M12-4P-T-R 10071081</p>
<p><b>NPN LED</b></p>	<p>2 signals per port NPN LED M23 vertical connector</p>	<p>JB4M12-4N-T-R 10071082</p>
<p><b>NO LED</b></p>	<p>2 signals per port NO LED Terminal connection</p>	<p>JB4M12-4-J-R 10071070</p>
<p><b>PNP LED</b></p>	<p>2 signals per port PNP LED Terminal connection</p>	<p>JB4M12-4P-J-R 10071071</p>
<p><b>NPN LED</b></p>	<p>2 signals per port NPN LED Terminal connection</p>	<p>JB4M12-4N-J-R 10071072</p>

\* Standard cable lengths are 2/5/10M, Consult factory for other lengths

\*\* Standard coupling nut material is nickel plated brass