

- Housing material: Nylon/Black
- Coupling nut: Brass/Nickel
- Contact carrier: TPU/Black
- Pin: Brass/Gold
- O-ring: FPM/FKM, IP degree: IP67
- Load: 10~30VDC, 2 A/port, 9 A total, LED 10mA
- Temperature range: -30...+80°C
- Mechanical operation: ≥100



Dimensions/Circuit diagram	Specifications	Type NO./ID NO.
<p>M23 12-Pin</p>	<p>1 signal per port NO LED M23 vertical connector</p>	<p>JB4M12-4-T 10071030</p>
<p>Terminal connection 21-Pin</p>	<p>1 signal per port PNP LED M23 vertical connector</p>	<p>JB4M12-4P-T 10071031</p>
<p>NPN LED</p>	<p>1 signal per port NPN LED M23 vertical connector</p>	<p>JB4M12-4N-T 10071032</p>
<p>NO LED</p>	<p>1 signal per port NO LED Terminal connection</p>	<p>JB4M12-4-J 10071020</p>
<p>PNP LED</p>	<p>1 signal per port PNP LED Terminal connection</p>	<p>JB4M12-4P-J 10071021</p>
<p>NPN LED</p>	<p>1 signal per port NPN LED Terminal connection</p>	<p>JB4M12-4N-J 10071022</p>

* Standard cable lengths are 2/5/10M, Consult factory for other lengths

** Standard coupling nut material is nickel plated brass