

## M12 8 ports Junction box

- Housing material:Nylon/Black
- Coupling nut:Brass/Nickel
- Contact carrier:TPU/Black
- Pin:Brass/Gold
- O-ring:FPM/FKM, IP degree:IP67
- Load:10~30VDC,2 A/port, 6 A total,LED 10mA
- Temperature range:-30...+80°C
- Mechanical operation:≥100



Dimensions/Circuit diagram	Specifications	Type NO./ID NO.
<p style="text-align: center;"><b>M23 19-Pin</b></p>	<p>2 signals per port NO LED M23 Horizontal connector</p>	<p>JB8M12-4-R 10073050</p>
	<p>2 signals per port PNP LED M23 Horizontal connector</p>	<p>JB8M12-4P-R 10073051</p>
	<p>2 signals per port NPN LED M23 Horizontal connector</p>	<p>JB8M12-4N-R 10073052</p>
<p style="text-align: right; font-size: small;"> <span style="color: blue;">■</span> Thread connection  <span style="color: red;">■</span> Cable connection  <span style="color: green;">■</span> Terminal connection         </p>	<p>2 signals per port No LED 2m Black 19 Wires 3x18AWG+16x22AWG Ø10.7mm PVC Cable Type NO. : CS192200-*M</p>	<p>JB8M12-4-D2-R 10073060</p>
	<p>2 signals per port PNP LED 2m Black 19 Wires 3x18AWG+16x22AWG Ø10.7mm PVC Cable Type NO. : CS192200-*M</p>	<p>JB8M12-4P-D2-R 10073061</p>
	<p>2 signals per port NPN LED 2m Black 19 Wires 3x18AWG+16x22AWG Ø10.7mm PVC Cable Type NO. : CS192200-*M</p>	<p>JB8M12-4N-D2-R 10073062</p>

\* Standard cable lengths are 2/5/10M, Consult factory for other lengths

\*\* Standard coupling nut material is nickel plated brass