

- Housing material: Oil resistant PUR material , Black
- Coupling nut: Brass/Nickel
- Contact carrier: TPU/Black
- Pin: Brass/Gold
- O-ring: FPM/FKM
- IP degree: IP67
- Temperature range: -30...+90°C
- Mechanical operation: ≥100



Connector type	Type NO.	ID NO.	Circuit diagram
	YSK4-2SZ3-2M-2M/P00 YSK4-2SZ3-5M-2M/P00 YSK4-2SZ3-10M-2M/P00	10014600 10014601 10014602	
	YSZ4-2SK3-2M-2M/P00 YSZ4-2SK3-5M-2M/P00 YSZ4-2SK3-10M-2M/P00	10014610 10014611 10014612	
	YK4-2EZ3-2M-2M/P00 YK4-2EZ3-5M-5M/P00 YK4-2EZ3-10M-10M/P00	10014000 10014001 10014002	
	YK4-2SZ3-2M-2M/P00 YK4-2SZ3-5M-5M/P00 YK4-2SZ3-10M-10M/P00	10014010 10014011 10014012	
	YZ4-2EK3-2M-2M/P00 YZ4-2EK3-5M-5M/P00 YZ4-2EK3-10M-10M/P00	10014020 10014021 10014022	
	YZ4-2SK3-2M-2M/P00 YZ4-2SK3-5M-5M/P00 YZ4-2SK3-10M-10M/P00	10014030 10014031 10014032	

* Standard cable lengths are 2/5/10M, Consult factory for other lengths

** Standard coupling nut material is nickel plated brass