

- Housing material:Nylon/Black
- Coupling nut:Brass/Nickel
- Contact carrier:TPU/Black
- Pin:Brass/Gold
- O-ring:FPM/FKM, IP degree:IP67
- Load:10~30VDC,2 A/port, 6 A total,LED 10mA
- Temperature range:-30...+80°C
- Mechanical operation:≥100



Dimensions/Circuit diagram	Specifications	Type NO./ID NO.
<p style="text-align: center;">4 1 3 3 M8</p> <p style="text-align: center;"> ■ Thread connection ■ Cable connection ■ Terminal connection </p>	<p>1 signal per port NO LED 2m Black 10 Wires 2x20AWG+8x24AWG PVC Ø8.0mm Cable Type NO. : CS102001-*M</p>	<p>JB8M8-3-D2 10073160</p>
<p style="text-align: center;">JB8M8-3-D2</p> <p style="text-align: center;">JB8M8-3P-D2</p>	<p>1 signal per port PNP LED 2m Black 10 Wires 2x20AWG+8x24AWG PVC Ø8.0mm Cable Type NO. : CS102001-*M</p>	<p>JB8M8-3P-D2 10073161</p>

* Standard cable lengths are 2/5/10M, Consult factory for other lengths

** Standard coupling nut material is nickel plated brass