



9	CLAMP NUT	NYLON	BLACK	1	
8	SEAL	SANTOPRENE, ID: 5.8mm.	BLACK	1	
7	HOOD	NYLON	BLACK	1	
6	S SEAL	SANTOPRENE.	BLACK	1	
5	O-RING	VITON.	BLACK	1	
4	SCREW NUT	NYLON+GF	BLACK	1	
3	CONTACT	BRASS, 6 u" GOLD PLATED. SOLDER BUCKET PIN.		n	
2	CONNECTOR	NYLON.		1	
1	O-RING	VITON	BROWN	1	
No.	PART NAME	DESCRIPTION	COLOR	QTY	REMARKS

REV.	DESCRIPTION	DATE
A	ISSUE	Sep/04/2008

- NOTES:
- ELECTRICAL CHARACTERISTICS:  
CURRENT RATING: 2A / 5A  
CONNECTOR TEMPERATURE RANGE: -40°C TO +105°C  
DIELECTRIC WITHSTANDING VOLTAGE:  
500V AC FOR ONE MINUTE
  - HOW TO ORDER: CAX-P2xxxSA

- 02 - 2 PINS    05 - 5 PINS
- 03 - 3 PINS    06 - 6 PINS
- 04 - 4 PINS
- D - CURRENT RATING 5A
- N - CURRENT RATING 2A

PIN ASSIGNMENT FRONT VIEW

CAD-P202SA

CAD-P203SA

CAN-P204SA

CAN-P205SA

CAN-P206SA

**HOLIN** HTP ASIA TECHNOLOGY CO., LTD.  
禾凌科技 股份有限公司

CIRCULAR A SIZE FEMALE SCREW TYPE FIELD-ATTACHABLE PLUG

SCALE: 1:1    UNIT: mm

P/N: CAX-P2xxxSA    DR: Stanley

CH: Mgrace    AP:

UNLESS OTHERWISE SPECIFIED TOLERANCES:  
X ±0.25    XX ± 0.1  
XXX ± 0.05    ANGLE ± 1&X

REV. SHEET: A    1/1    DWG. NO.: CAX-P2xxxSA